NASA PATENT ABSTRACTS BIBLIOGRAPHY

A CONTINUING BIBLIOGRAPHY



NASA STI Program ... in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program plays a key part in helping NASA maintain this important role.

The NASA STI Program provides access to the NASA Aeronautics and Space Database, the largest collection of aeronautical and space science in the world. The STI Program is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- TECHNICAL PUBLICATION. Reports of completed research or major significant phases of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed of continuing reference value. NASA counterpart of peer-reviewed formal professional papers, but has less stringent limitations on manuscript length and extent of graphic presentations.
- TECHNICAL MEMORANDUM. Scientific and technical findings that are of preliminary or specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- CONTRACTOR REPORT. Scientific and technical findings by NASA-sponsored contractors and grantees.
- CONFERENCE PUBLICATION. Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or co-sponsored by NASA.

- SPECIAL PUBLICATION. Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- TECHNICAL TRANSLATION. Englishlanguage translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that help round out the STI Program's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results ... even providing videos.

The NASA STI Program is managed by the NASA STI Program Office (STIPO). STIPO is the administrative office at Langley Research Center for the NASA STI Program.

For more information about the NASA STI Program, you can:

- Access the NASA STI Program Home Page at http://www.sti.nasa.gov
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA STI Help Desk at (301) 621-0134
- Telephone the NASA STI Help Desk at (301) 621-0390
- Write to: NASA STI Help Desk
 NASA Center for AeroSpace Information
 7121 Standard Drive
 Hanover, MD 21076-1320

Introduction

Several thousand inventions result each year from research supported by the National Aeronautics and Space Administration. NASA seeks patent protection on inventions to which it has title if the invention has important use in government programs or significant commercial potential. These inventions cover a broad range of technologies and include many that have useful and valuable commercial application.

NASA inventions best serve the interests of the United States when their benefits are available to the public. In many instances, the granting of nonexclusive or exclusive licenses for the practice of these inventions may assist in the accomplishment of this objective. This bibliography is published as a service to companies, firms, and individuals seeking new, licensable products for the commercial market.

The NASA Patent Abstracts Bibliography is a semiannual NASA publication containing comprehensive abstracts of NASA-owned inventions covered by U.S. patents. The citations included were originally published in NASA's Scientific and Technical Aerospace Reports (STAR) and cover STAR announcements made since May 1969.

The citations published in this issue cover the period July 2004 through December 2004. The range of subjects covered includes the NASA Scope and Subject Category Guide's 10 broad subject divisions separated further into 76 specific categories. However, not all categories have citations during the dates covered for this issue, therefore the Table of Contents does not include all divisions and categories. This scheme was devised in 1975 and revised in 1987 and 2000 in lieu of the 34 category divisions which were utilized in supplements (01) through (06) covering *STAR* abstracts from May 1969 through January 1974. Each entry consists of a citation accompanied by an abstract and, when appropriate, a key illustration taken from the patent or application for patent. Entries are arranged by subject category in ascending order.

Information About Patent Availability and Licenses

Patent Availability

How to obtain copies of NASA patents.

Licenses for Commercial Use

Information on obtaining a license to use a NASA patented invention.

Address of NASA Patent Counsels

Addresses for the NASA center patent counsels having knowledge of the invention.

Patent Licensing Regulations

Information about the policies and procedures for licensing federally owned inventions in the custody of the National Aeronautics and Space Administration. Regulations on the licensing of government-owned inventions are available at: http://www.access.gpo.gov/nara/cfr/waisidx 02/37cfr404 02.html.

The Federal Depository Library Program

The U.S. Congress established the **Federal Depository Library Program** (FDLP) to ensure access by the American public to U.S. Government information. The program acquires and disseminates information products from all three branches of the U.S. Government to nearly 1,300 Federal depository libraries nationwide. The libraries maintain these information products as part of their existing collections and are responsible for assuring that the public has free access to the information. Locate the Federal Depository Libraries at: http://www.gpoaccess.gov/libraries.html.

Table of Contents

Subject Divisions/Categories

Document citations are grouped by division and then by category, according to the NASA Scope and Coverage Category Guide.

Aerona	utics
0	3 Air Transportation and Safety
Astron	autics
2	0 Spacecraft Propulsion and Power
Chemis	stry and Materials
2	3 Chemistry and Materials (General)
2	4 Composite Materials
2	6 Metals and Metallic Materials
Engine	ering
3	3 Electronics and Electrical Engineering
3	4 Fluid Mechanics and Thermodynamics
3	5 Instrumentation and Photography 9
3	7 Mechanical Engineering 14
3	8 Quality Assurance and Reliability
Life Sc	iences
5	1 Life Sciences (General)
5	2 Aerospace Medicine
Mathen	natical and Computer Sciences
6	1 Computer Programming and Software
Physics	S
7	4 Optics
7	6 Solid-State Physics

Indexes

Two indexes are available. You may use the find command under the tools menu while viewing the PDF file for direct match searching on any text string. You may also select either of the two indexes provided for linking to the corresponding document citation from *NASA Thesaurus* terms and personal author names.

Subject Term Index Personal Author Index

NASA PATENT ABSTRACTS BIBLIOGRAPHY

A Continuing Bibliography (Suppl. 65)

JANUARY 2005

03 AIR TRANSPORTATION AND SAFETY

Includes passenger and cargo air transport operations; airport ground operations; flight safety and hazards; and aircraft accidents. Systems and hardware specific to ground operations of aircraft and to airport construction are covered in 09 Research and Support Facilities (Air). Air traffic control is covered in 04 Aircraft Communications and Navigation. For related information see also 16 Space Transportation and Safety and 85 Technology Utilization and Surface Transportation.


20040120989 NASA Marshall Space Flight Center, Huntsville, AL, USA **Article Screening System**

Fernandez, Kenneth R., Inventor; July 13, 2004; 8 pp.; In English; Original contains black and white illustrations Patent Info.: Filed 30 Aug. 2002; US-Patent-6,763,083; US-Patent-Appl-SN-232937; NASA-Case-MFS-31783-1; No Copyright; Avail: CASI; A02, Hardcopy

During the last ten years patents directed to luggage scanning apparatus began to appear in the patent art. Absent from the variety of approaches in the art is stereoscopic imaging that entails exposing two or more images of the same object, each taken from a slightly different perspective. If the perspectives are too different, that is. if there is too much separation of the X-ray exposures, the image will look flat. Yet with a slight separation, a stereo separation, interference occurs. Herein a system is provided for the production of stereo pairs. One perspective, a left or a right perspective angle, is first established. Next, the other perspective angle is computed. Using these left and right perspectives the X-ray sources can then be spaced away from each other.

Author

Baggage; Imaging Techniques; Stereoscopy; X Ray Imagery



20 SPACECRAFT PROPULSION AND POWER

Includes main propulsion systems and components, e.g., rocket engines; and spacecraft auxiliary power sources. For related information see also 07 Aircraft Propulsion and Power, 28 Propellants and Fuels, 15 Launch Vehicles and Launch Operations, and 44 Energy Production and Conversion.

20040120977 NASA Glenn Research Center, Cleveland, OH, USA


Method for Forming MEMS-Based Spinning Nozzle

Okojie, Robert S., Inventor; August 03, 2004; 9 pp.; In English; Original contains black and white illustrations Patent Info.: Filed 13 Aug. 2002; US-Patent-6,770,208; US-Patent-Appl-SN-219385; US-Patent-Appl-SN-816722; NASA-Case-LEW-17110-2; No Copyright; Avail: CASI; A02, Hardcopy

A nozzle body and assembly for delivering atomized fuel to a combustion chamber. The nozzle body is rotatably mounted onto a substrate. One or more curvilinear fuel delivery channels are in flow communication with an internal fuel distribution cavity formed in the nozzle body. Passage of pressurized fuel through the nozzle body causes the nozzle body to rotate. Components of the nozzle assembly are formed of silicon carbide having surfaces etched by deep reactive ion etching utilizing MEMS technology. A fuel premix chamber is carried on the substrate in flow communication with a supply passage in the nozzle body.

Author

Fabrication; Spray Nozzles; Microelectromechanical Systems; Fuel Injection; Atomizers; Fuel Sprays



23 CHEMISTRY AND MATERIALS (GENERAL)

Includes general research topics related to the composition, properties, structure, and use of chemical compounds and materials as they relate to aircraft, launch vehicles, and spacecraft. For specific topics in chemistry and materials see *categories 25 through 29*. For astrochemistry see category *90 Astrophysics*.

20040120974 NASA Langley Research Center, Hampton, VA, USA

Heat, Moisture and Chemical Resistant Polyimide Compositions and Methods for Making and Using Them Pater, Ruth H., Inventor; August 17, 2004; 12 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 1 Apr. 2002; US-Patent-6,777,525; US-Patent-Appl-SN-115812; US-Patent-Appl-SN-303741; NASA-Case-LAR-16311-1; No Copyright; Avail: CASI; A03, Hardcopy

Polyimides having a desired combination of high thermo-oxidative stability, low moisture absorption and excellent chemical and corrosion resistance are prepared by reacting a mixture of compounds including (a) 3,3',4,4'-benzophenonetetracarboxylic dianhydride (BTDA), (b) 3,4'-oxydianiline (3,4'-ODA), and (c) 5-norbornene-2,3- dicarboxylic anhydride (NA) in a high boiling, aprotic solvent to give 5 to 35% by weight of polyamic acid solution. The ratio of (a), (b), and (c) is selected to afford a family of polyimides having different molecular weights and properties. The mixture first forms a polyamic acid precursor. Upon heating at or above 300 C, the polyamic acids form polyimides, which are particularly suitable for use as a high temperature coating, adhesive, thin film, or composite matrix resin.

Author

Synthesis (Chemistry); Polyimides

20040120975 NASA Marshall Space Flight Center, Huntsville, AL, USA

Dual Use Corrosion Inhibitor and Penetrant for Anomaly Detection in Neutron/X Radiography


Hall, Phillip B., Inventor; Novak, Howard L., Inventor; August 17, 2004; 5 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 27 Nov. 2001; US-Patent-6,777,238; US-Patent-Appl-SN-011228; NASA-Case-MFS-31562-1; No Copyright; Avail: CASI; A01, Hardcopy

A dual purpose corrosion inhibitor and penetrant composition sensitive to radiography interrogation is provided. The corrosion inhibitor mitigates or eliminates corrosion on the surface of a substrate upon which the corrosion inhibitor is applied. In addition, the corrosion inhibitor provides for the attenuation of a signal used during radiography interrogation thereby providing for detection of anomalies on the surface of the substrate.

Author

Corrosion Prevention; Penetrants; Radiography; Coatings



20040121007 NASA Glenn Research Center, Cleveland, OH, USA


Multilayer Article Characterized by Low Coefficient of Thermal Expansion Outer Layer

Lee, Kang N., Inventor; July 06, 2004; 18 pp.; In English; Original contains black and white illustrations Patent Info.: Filed 22 May 2002; US-Patent-6,759,151; US-Patent-Appl-SN-154526; NASA-Case-LEW-17275-1; No Copyright; Avail: CASI; A03, Hardcopy

A multilayer article comprises a substrate comprising a ceramic or a silicon-containing metal alloy. The ceramic is a Si-containing ceramic or an oxide ceramic with or without silicon. An outer layer overlies the substrate and at least one intermediate layer is located between the outer layer and the substrate. An optional bond layer is disposed between the 1 least one intermediate layer and optional chemical barrier layer adjacent the outer layer, a mullite-containing layer and an optional chemical barrier layer adjacent to the bond layer or substrate. The outer layer comprises a compound having a low coefficient of thermal expansion selected from one of the following systems: rare earth (RE) silicates; at least one of hafnia and hafnia-containing composite oxides; zirconia-containing composite oxides and combinations thereof.

Author

Thermal Expansion; Barrier Layers; Silicates; Zirconium Oxides



24 COMPOSITE MATERIALS

Includes physical, chemical, and mechanical properties of laminates and other composite materials.

20040120980 NASA Kennedy Space Center, Cocoa Beach, FL, USA


Ferromagnetic Conducting Lignosulfonic Acid-doped Polyaniline Nanocomposites

Viswansthan, Tito, Inventor; Berry, Brian, Inventor; July 20, 2004; 13 pp.; In English

Patent Info.: Filed 16 Nov. 2001; US-Patent-6,764,617; US-Patent-Appl-SN-994996; US-Patent-Appl-SN-249563; NASA-Case-KSC-12190-1; No Copyright; Avail: CASI; A03, Hardcopy

A conductive ferromagnetic composition of matter comprising sulfonated lignin or a sulfonated polyflavonoid, or derivatives thereof, and ferromagnetic iron oxide particles is disclosed. Among the uses of the composition is to shield electromagnetic radiation. The ferromagnetic iron oxide particles of the composition are surprisingly stable to acid, and are easily and inexpensively formed from iron cations in solution.

Author
Nanocomposites; Ferromagnetic Materials; Sulfonic Acid



26
METALS AND METALLIC MATERIALS

Includes physical, chemical, and mechanical properties of metals and metallic materials; and metallurgy.

20040121004 NASA Langley Research Center, Hampton, VA, USA

Process for Coating Substrates with Catalytic Materials

Klelin, Ric J., Inventor; Upchurch, Billy T., Inventor; Schryer, David R., Inventor; June 22, 2004; 6 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 30 Jun. 2000; US-Patent-6,753,293; US-Patent-Appl-SN-607211; No Copyright; Avail: CASI; A02, Hardcopy

A process for forming catalysts by coating substrates with two or more catalytic components, which comprises the following sequence of steps. First, the substrate is infused with an adequate amount of solution having a starting material comprising a catalytic component precursor, wherein the thermal decomposition product of the catalytic component precursor is a catalytic component. Second, the excess of the solution is removed from the substrate. thereby leaving a coating of the catalytic component precursor on the surface of the substrate. Third, the coating of the catalytic component precursor is converted to the catalytic component by thermal decomposition. Finally, the coated substance is etched to increase the surface area. The list three steps are then repeated for at least a second catalytic component. This process is ideally suited for application in producing efficient low temperature oxidation catalysts.

Author

Catalysts; Coating; Substrates

33 ELECTRONICS AND ELECTRICAL ENGINEERING

Includes development, performance, and maintainability of electrical/electronic devices and components; related test equipment; and microelectronics and integrated circuitry. for related information see also 60 Computer Operations and Hardware; and 76 Solid-State Physics. For communications equipment and devices see 32 Communications and Radar.

20040081216 NASA Langley Research Center, Hampton, VA, USA


Synchronized Electronic Shutter System and Method for Thermal Nondestructive Evaluation

Zalameda, Joseph N., Inventor; Winfree, William P., Inventor; March 30, 2004; 28 pp.; In English

Patent Info.: Filed 10 Apr. 2002; US-Patent-6,712,502; US-Patent-Appl-SN-120225; NASA-Case-LAR-16126-1; No Copyright; Avail: CASI; A03, Hardcopy

The invention is a synchronized electronic shutter system (SESS) and method for same side and through transmission thermal analysis and inspection of a material for finding defects, corrosion, disbond defects, integrity of a weld and determination of paint thickness. The system comprises an infrared detector that acquires background images of the sample. A shutter then covers the detector and lamps rapidly heat the sample above ambient temperature. Shutters cover all lamps at the same time the shutter over the infrared detector is opened. The infrared detector acquires a series of temperature images over time radiated from the sample a s the sample cools down. After collecting a series of temperature images taken by the SESS, a processed image is developed using one of the group comprising time derivative calculation, temperature normalization data reduction routine, thermal diffusivity curve fitting and averaging the series of temperature images. Author

Synchronizers; Shutters; Nondestructive Tests; Thermal Analysis



20040120978 NASA Glenn Research Center, Cleveland, OH, USA

Multi-Functional, Micro Electromechanical Silicon Carbide Accelerometer


Okojie, Robert S., Inventor; August 03, 2004; 39 pp.; In English; Original contains black and white illustrations Patent Info.: Filed 24 Sep. 2003; US-Patent-6,769,303; US-Patent-Appl-SN-669587; US-Patent-Appl-SN-124689; NASA-Case-LEW-17170-2; No Copyright; Avail: CASI; A03, Hardcopy

A method of bulk manufacturing SiC sensors is disclosed and claimed. Materials other than SiC may be used as the substrate material. Sensors requiring that the SiC substrate be pierced are also disclosed and claimed. A process flow reversal is employed whereby the metallization is applied first before the recesses are etched into or through the wafer. Aluminum is deposited on the entire planar surface of the metallization. Photoresist is spun onto the substantially planar surface of the Aluminum which is subsequently masked (and developed and removed). Unwanted Aluminum is etched with aqueous TMAH and subsequently the metallization is dry etched. Photoresist is spun onto the still substantially planar surface of Aluminum and oxide and then masked (and developed and removed) leaving the unimidized photoresist behind. Next, ITO is applied over the still substantially planar surface of Aluminum, oxide and unimidized photoresist. Unimidized and exposed photoresist and ITO directly above it are removed with Acetone. Next, deep reactive ion etching attacks exposed oxide not protected by ITO.

Finally, hot phosphoric acid removes the Al and ITO enabling wires to connect with the metallization. The back side of the SiS wafer may be also etched.

Official Gazette of the U.S. Patent and Trademark Office

Accelerometers; Silicon Carbides; Microelectromechanical Systems; Manufacturing



20040120984 NASA Pasadena Office, CA, USA


Method for Manufacturing Thin-film Lithium Microbatteries

Whitacre, Jay F., Inventor; Bugga, Ratnakumar V., Inventor; West, William C., Inventor; July 20, 2004; 14 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 11 Mar. 2003; US-Patent-6,764,525; US-Patent-Appl-SN-390258; US-Patent-Appl-SN-779595; NASA-Case-NPO-21015-2-CU; No Copyright; Avail: CASI; A03, Hardcopy

A process for making thin-film batteries including the steps of cleaning a glass or silicon substrate having an amorphous oxide layer several microns thick; defining with a mask the layer shape when depositing cobalt as an adhesion layer and platinum as a current collector; using the same mask as the preceding step to sputter a layer of LiCoO2 on the structure while rocking it back and forth; heating the substrate to 300 C. for 30 minutes; sputtering with a new mask that defines the necessary electrolyte area; evaporating lithium metal anodes using an appropriate shadow mask; and, packaging the cell in a dry-room environment by applying a continuous bead of epoxy around the active cell areas and resting a glass slide over the top thereof. Official Gazette of the U.S. Patent and Trademark Office

Thin Films; Lithium Batteries; Manufacturing



20040120995 NASA Pasadena Office, CA, USA


Protective Fullerene (C60) Packaging System for Microelectromechanical Systems Applications

Olivas, John D., Inventor; September 14, 2004; 7 pp.; In English; Original contains black and white illustrations Patent Info.: Filed 20 Jun. 2001; US-Patent-6,791,108; US-Patent-Appl-SN-888631; US-Patent-Appl-SN-310774; NASA-Case-NPO-20148-2; No Copyright; Avail: CASI; A02, Hardcopy

The invention involves tunneling tips to their conducting surface, and specifically the deposition of a monolayer of fullerene C60 onto the conducting plate surface to protect the tunneling tip from contact. The Fullerene C60 molecule is approximately spherical, and a monolayer of fullerene has a thickness of one nanometer, such that a monolayer thereby establishing the theoretical distance desired between the MEMS tunneling tip and the conducting plate. Exploiting the electrical conductivity of C60 the tip can be accurately positioned by simply monitoring conductivity between the fullerene and the tunneling tip. By monitoring the Conductivity between the tip and the fullerene layer as the tip is brought in proximity, the surfaces can be brought together without risk of contacting the underlying conducting surface. Once the tunneling tip is

positioned at the one nanometer spacing, with only the monolayer of fullerene between the tunneling tip and the conducting plate, the monolayer of C60, can be broken down thermally and removed chemically leaving only the tunneling tip and the conducting plate at the ideal tunneling spacing. Alternatively, the properties of fullerene allow the tunneling process to occur directly across the fullerene monolayer.

Official Gazette of the U.S. Patent and Trademark Office Fullerenes; Microelectromechanical Systems; Packaging



20040121000 NASA Marshall Space Flight Center, Huntsville, AL, USA

Cross Cell Sandwich Core


Ford, Donald B., Inventor; June 08, 2004; 5 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 6 Aug. 2001; US-Patent-6,745,662; US-Patent-Appl-SN-922169; NASA-Case-MFS-31613-1; No Copyright; Avail: CASI; A01, Hardcopy

A sandwich core comprises two faceplates separated by a plurality of cells. The cells are comprised of walls positioned at oblique angles relative to a perpendicular axis extending through the faceplates. The walls preferably form open cells and are constructed from open cells and are constructed from rows of ribbons. The walls may be obliquely angled relative to more than one plane extending through the perpendicular axis.

Author

Walls; Electrolytic Cells



20040121002 NASA Pasadena Office, CA, USA

Very High Efficiency, Miniaturized, Long-Lived Alpha Particle Power Source Using Diamond Devices for Extreme Space Environments


Kolawa, Elizabeth A., Inventor; Patel, Jagdishbhai U., Inventor; Fleurial, Jean-Pierre, Inventor; June 22, 2004; 6 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 5 Aug. 2002; US-Patent-6,753,469; US-Patent-Appl-SN-214486; NASA-Case-NPO-30323; No Copyright; Avail: CASI; A02, Hardcopy

A power source that converts a-particle energy into electricity by coulomb collision in doped diamond films is described. Alpha particle decay from curium-244 creates electron-hole pairs by free- ing electrons and holes inside the crystal lattice in N- and P-doped diamond films. Ohmic contacts provide electrical connection to an electronic device. Due to the built-in electric field at the rectifying junction across the hT- and P-doped diamond films, the free electrons are constrained to traveling in generally one direction. This one direction then supplies electrons in a manner similar to that of a battery. The radioactive curium layer may be disposed on diamond films for even distribution of a-particle radiation. The resulting power source may be mounted on a diamond substrate that serves to insulate structures below the diamond substrate from a-particle emission. Additional insulation or isolation may be provided in order to prevent damage from a-particle collision. N-doped silicon may be used instead of N-doped diamond.

Author

Alpha Particles; Diamond Films; Electric Power Supplies



34 FLUID MECHANICS AND THERMODYNAMICS

Includes fluid dynamics and kinematics and all forms of heat transfer; boundary layer flow; hydrodynamics; hydraulics; fluidics; mass transfer and ablation cooling. For related information see also *02 Aerodynamics*.

20040081214 NASA Kennedy Space Center, Cocoa Beach, FL, USA

Apparatus and Method for Thermal Performance Testing of Pipelines and Piping Systems


Fesmire, James E., Inventor; Nagy, Zeltan F., Inventor; Augustynowicz, Stanislaw D., Inventor; April 06, 2004; 8 pp.; In English

Patent Info.: Filed 26 Jun. 2002; US-Patent-6,715,914; US-Patent-Appl-SN-185378; NASA-Case-KSC-12205; No Copyright; Avail: CASI; A02, Hardcopy

A test apparatus and method of its use for evaluating various performance aspects of a piping segment locates a piping segment between two cold boxes. A first cold box conditions test fluid before providing the fluid into the piping segment. The first and second cold boxes both significantly reduce, if not eliminate, any heat transfer from the ends of the piping so that accurate measurements of heat leak rates from the sides of the piping segment may be determined.

Author

Performance Tests; Pipelines; Heat Transfer



20040081215 NASA Langley Research Center, Hampton, VA, USA

Self-Activating System and Method for Alerting When an Object or a Person is Left Unattended


Edwards, William Christopher, Inventor; Mack, Terry L., Inventor; Modlin, Edward A., Inventor; March 30, 2004; 22 pp.; In English

Patent Info.: Filed 27 Nov. 2001; US-Patent-6,714,132; US-Patent-Appl-SN-011229; US-Patent-Appl-SN-329692; NASA-Case-LAR-16324-1; No Copyright; Avail: CASI; A03, Hardcopy

A system and method uses a wireless tether comprising a transmitter and a receiver to alert a caregiver that an object or person has been left unattended. A detector Senses the presence of the object, usually a child, located in a position such as a safety seat. The detector couples to the transmitter, which is located near the object. The transmitter transmits at least one wireless signal when the object is in the position. The receiver, which is remotely located from the transmitter, senses the at least one signal as long as the receiver is within a prescribed range of transmission. By performing a timing function, the receiver monitors the proximity of the caregiver, who maintains possession of the receiver, to the transmitter. The system communicates an alarm to the caregiver when the caregiver ventures outside the range of transmission without having removed the object/child from the position.

Author

Warning Systems; Monitors; Safety



35
INSTRUMENTATION AND PHOTOGRAPHY

Includes remote sensors; measuring instruments and gages; detectors; cameras and photographic supplies; and holography. For aerial photography see 43 Earth Resources and Remote Sensing. For related information see also 06 Avionics and Aircraft Instrumentation; and 19 Spacecraft Instrumentation and Astrionics.

20040120979 NASA Langley Research Center, Hampton, VA, USA

Multi-Element Electron-Transfer Optical Detector System


Jordan, Jeffrey D., Inventor; July 20, 2004; 6 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 13 Mar. 2002; US-Patent-6,765,190; US-Patent-Appl-SN-097699; US-Patent-Appl-SN-276568; NASA-Case-LAR-16279-2; No Copyright; Avail: CASI; A02, Hardcopy

A multi-element optical detector system includes an electrically resistive screen that is substantially transparent to radiation energy having a wavelength of interest. A plurality of electron transfer elements (e.g., a low work function photoactive material or a carbon nanotube (CNT)-based element) are provided with each having a first end and a second end. The first end of each element is spaced apart from the screen by an evacuated gap. When the radiation energy passes through

the screen with a bias voltage applied thereto, transfer of electrons through each element is induced from the first end to the second end such that a quantity indicative of the electrons transferred through each element can be detected. Author

Optical Equipment; Radiation Detectors; Electron Transfer



20040120991 NASA Langley Research Center, Hampton, VA, USA

Method and Apparatus for Non-Invasive Measurement of Changes in Intracranial Pressure


Yost, William T., Inventor; Cantrell, John H., Jr., Inventor; July 13, 2004; 9 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 7 Mar, 2002; US-Patent-6,761,695; US-Patent-Appl-SN-094,023; NASA-Case-LAR-15854-1; No Copyright; Avail: CASI; A02, Hardcopy

A method and apparatus for measuring intracranial pressure. In one embodiment, the method comprises the steps of generating an information signal that comprises components (e.g., pulsatile changes and slow changes) that are related to intracranial pressure and blood pressure, generating a reference signal comprising pulsatile components that are solely related to blood pressure, processing the information and reference signals to determine the pulsatile components of the information signal that have generally the same phase as the pulsatile components of the reference signal, and removing from the information signal the pulsatile components determined to have generally the same phase as the pulsatile components of the reference signal so as to provide a data signal having components wherein substantially all of the components are related to intracranial pressure.

Author

Intracranial Pressure; Pressure Measurement; Nonintrusive Measurement; Medical Equipment



20040120993 NASA Kennedy Space Center, Cocoa Beach, FL, USA


Thermodynamic Pressure/Temperature Transducer Health Check

Immer, Christopher D., Inventor; Eckhoff, Anthony, Inventor; Medelius, Pedro J., Inventor; Deyoe, Richard T., Inventor; Starr, Stanley O., Inventor; August 31, 2004; 14 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 9 Nov. 2001; US-Patent-6,782,753; US-Patent-Appl-SN-994990; US-Patent-Appl-SN-247848; NASA-Case-KSC-12139-1; No Copyright; Avail: CASI; A03, Hardcopy

A device and procedure for checking the health of a pressure transducer in situ is provided. The procedure includes measuring a fixed change in pressure above ambient pressure and a fixed change in pressure below ambient pressure. This is done by first sealing an enclosed volume around the transducer with a valve. A piston inside the sealed volume is increasing the pressure. A fixed pressure below ambient pressure is obtained by opening the valve, driving the piston The output of the pressure transducer is recorded for both the overpressuring and the underpressuring. By comparing this data with data taken during a preoperative calibration, the health of the transducer is determined from the linearity, the hysteresis, and the repeatability of its output. The further addition of a thermometer allows constant offset error in the transducer output to be determined.

Official Gazette of the U.S. Patent and Trademark Office Thermodynamics; Pressure Sensors; Thermometers; Health



20040120997 NASA Glenn Research Center, Cleveland, OH, USA

Rare Earth Optical Temperature Sensor

Chubb, Donald L., Inventor; Jenkins, Phillip, Inventor; June 08, 2004; 4 pp.; In English; Original contains black and white illustrations


Patent Info.: Filed 1 Jun. 1999; US-Patent-6,746,149; US-Patent-Appl-SN-323650; NASA-Case-LEW-16682-1; No Copyright; Avail: CASI; A01, Hardcopy

A rare earth optical temperature sensor is disclosed for measuring high temperatures. Optical temperature sensors exist that channel emissions from a sensor to a detector using a light pipe. The invention uses a rare earth emitter to transform the

sensed thermal energy into a narrow band width optical signal that travels to a detector using a light pipe. An optical bandpass filter at the detector removes any noise signal outside of the band width of the signal from the emitter.

Official Gazette of the U.S. Patent and Trademark Office

Rare Earth Elements; Temperature Sensors; Optical Measuring Instruments; Manufacturing




20040120998 NASA Pasadena Office, CA, USA

Heterodyne Interferometer with a Phase Modulated Source

Dubovitsky, Serge, Inventor; September 07, 2004; 7 pp.; In English; Original contains black and white illustrations Patent Info.: Filed 7 Sep. 2004; US-Patent-6,788,420; US-Patent-Appl-SN-061067; NASA-Case-NPO-20740; No Copyright; Avail: CASI; A02, Hardcopy

The present invention relates to a heterodyne interferometer system with a pre-processing of the target signal to isolate and remove self-interference signals using a known phase modulation of the carrier signal's frequency. Where self-interference signals do not include a time delay inherent in the target signal that travels to the target reflector, by selecting a modulation frequency tuned to the time delay and then filtering the resultant signal the target beam can be isolated and the self-interference signal can be effectively removed The system includes a modulation unit to apply a phase modulation to the carrier signal, and a mixing unit that demodulates the target signal at the modulation frequency to isolate the target beam. Author

Heterodyning; Interferometers; Phase Modulation




20040121008 NASA Ames Research Center, Moffett Field, CA, USA

Retinal Light Processing Using Carbon Nanotubes

Loftus, David J., Inventor; Leng, Theodore, Inventor; Fishman, Harvey, Inventor; June 29, 2004; 15 pp.; In English Patent Info.: Filed 16 Jul. 2002; US-Patent-6,755,530; US-Patent-Appl-SN-198672; NASA-Case-ARC-14941-1; No Copyright; Avail: CASI; A03, Hardcopy

Method and system for processing light signals received by the eye of a human or other animal, where the eye may be compromised or non-functioning. Incident light is received at first and second pixels in a photodetector array and provides a pixel electrical signal representing the received light. Each of an array of carbon nanotube (CNT) towers is connected to a pixel, has a first tower end penetrating a retinal active layer of the animal and has a second tower end positioned to receive to receive and transport the pixel electrical signal to the retinal active layer. The CNT tower may be coated with a biologically active substance or chemically modified to promote neurite connections with the tower. The photoreceptor array can be provide with a signal altering mechanism that alters at least one of light intensity and wavelength intensity sensed by a first pixel relative to a second pixel, to correct for one or more selected eye problems.

Carbon Nanotubes; Enhanced Vision; Retina; Bioinstrumentation



20040121125 NASA Langley Research Center, Hampton, VA, USA Single-element Electron-transfer Optical Detector System


Jordan, Jeffrey D., Inventor; June 15, 2004; 12 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 13 Mar. 2002; US-Patent-6,750,438; US-Patent-Appl-SN-097702; US-Patent-Appl-SN-276568; NASA-Case-LAR-16279-1; No Copyright; Avail: CASI; A03, Hardcopy

An optical detector system includes an electrically resistive screen that is substantially transparent to radiation energy having a wavelength of interest. An electron transfer element (e.g., a low work function photoactive material or a carbon nanotube (CNT)-based element) has a first end and a second end with its first end spaced apart from the screen by an evacuated gap. When radiation energy passes through the screen with a bias voltage being applied thereto, transfer of electrons through the electron transfer element is induced from its first to its second end such that a quantity indicative of the electrons transferred can be detected.

Author

Electron Counters; Carbon Nanotubes; Electron Transfer



20040129681 NASA Marshall Space Flight Center, Huntsville, AL, USA


Video Image Tracking Engine

Howard, Richard T., Inventor; Bryan, Thomas C., Inventor; Book, Michael L., Inventor; August 17, 2004; 9 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 28 Sep. 2001; US-Patent-6,778,180; US-Patent-Appl-SN-967833; NASA-Case-MFS-31525-1; No Copyright; Avail: CASI; A02, Hardcopy

A method and system for processing an image including capturing an image and storing the image as image pixel data. Each image pixel datum is stored in a respective memory location having a corresponding address. Threshold pixel data is selected from the image pixel data and linear spot segments are identified from the threshold pixel data selected. Ihe positions of only a first pixel and a last pixel for each linear segment are saved. Movement of one or more objects are tracked by comparing the positions of fust and last pixels of a linear segment present in the captured image with respective first and last pixel positions in subsequent captured images. Alternatively, additional data for each linear data segment is saved such as sum of pixels and the weighted sum of pixels i.e., each threshold pixel value is multiplied by that pixel's x-location). Author

Video Equipment; Image Processing; Video Data



37 MECHANICAL ENGINEERING

Includes mechanical devices and equipment; machine elements and processes. For cases where the application of a device or the host vehicle is emphasized see also the specific category where the application or vehicle is treated. For robotics see *63 Cybernetics, Artificial Intelligence, and Robotics*; and *54 Man/System Technology and Life Support.*

20040120988 NASA Glenn Research Center, Cleveland, OH, USA

Gas Sensors Using SiC Semiconductors and Method of Fabrication Thereof


Hunter, Gary W., Inventor; Neudeck, Philip G., Inventor; July 20, 2004; 18 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 6 Feb. 2003; US-Patent-6,763,699; US-Patent-Appl-SN-359940; NASA-Case-LEW-17300-1; No Copyright; Avail: CASI; A03, Hardcopy

Gas sensor devices are provided having an atomically flat silicon carbide top surface that, in turn, provides for a uniform, and reproducible surface thereof.

Official Gazette of the U.S. Patent and Trademark Office

Fabrication; Gas Detectors; Semiconductors (Materials); Silicon Carbides



20040120992 NASA Glenn Research Center, Cleveland, OH, USA


Auto-Adjustable Tool for Self-Reacting and Conventional Friction Stir Welding

Carter, Robert W., Inventor; April 30, 2002; 6 pp.; In English; Original contains black and white illustrations Patent Info.: Filed 2 May 2003; US-Patent-6,758,382; US-Patent-Appl-SN-431655; NASA-Case-LEW-16056-3 Report No.(s): SHINe; No Copyright; Avail: CASI; A02, Hardcopy

A friction stir welding device that is configured to perform convention friction stir welding as well as self-reacting friction stir welding is described. A pin passes brough an upper shoulder and can selectively attach 10 and detach from a lower shoulder in a preferred embodiment. A controller maintains the discrete position of, and/or force applied by, the upper and lower shoulders during self-reacting friction stir welding, or maintains the pin at a desired depth and/or applied force during conventional friction stir welding.

Author

Friction Stir Welding; Diagrams



20040120999 NASA Dryden Flight Research Center, Edwards, CA, USA

Force-Measuring Clamp


Nunnelee, Mark, Inventor; July 06, 2004; 10 pp.; In English; Original contains black and white illustrations Patent Info.: Filed 20 Feb. 2002; US-Patent-6,758,098; US-Patent-Appl-SN-084747; NASA-Case-DRC-099037; No Copyright; Avail: CASI; A02, Hardcopy

A precision clamp that accurately measures force over a wide range of conditions is described. Using a full bridge or other strain gage configuration, the elastic deformation of the clamp is measured or detected by the strain gages. The strain gages

transmit a signal that corresponds to the degree of stress upon the clamp. The strain gage signal is converted to a numeric display. Calibration is achieved by ero and span potentiometers which enable accurate measurements by the force-measuring clamp.

Author

Strain Gages; Clamps



38
QUALITY ASSURANCE AND RELIABILITY

Includes approaches to, and methods for reliability analysis and control, quality control, inspection, maintainability, and standardization.

20040081248 NASA Kennedy Space Center, Cocoa Beach, FL, USA


Methods of Testing Thermal Insulation and Associated Test Apparatus

June 1, 2004; 15 pp.; In English

Patent Info.: Filed 10 Jul. 2001; US-Patent-6,742,926; US-Patent-Appl-SN-217121; NASA-Case-KSC-12107; No Copyright; Avail: CASI; A03, Hardcopy

The system and method for testing thermal insulation uses a cryostatic insulation tester having a vacuum chamber and a cold mass including a test chamber and upper and lower guard chambers adjacent thereto. The thermal insulation is positioned within the vacuum chamber and adjacent the cold mass. Cryogenic liquid is supplied to the test chamber, upper guard and lower guard to create a first gas layer in an upper portion of the lower guard chamber and a second gas layer in an upper portion of the test chamber. Temperature are sensed within the vacuum chamber to test the thermal insulation. Author

Thermal Insulation; Cryogenics



51 LIFE SCIENCES (GENERAL)

Includes general research topics related to plant and animal biology (non-human); ecology; microbiology; and also the origin, development, structure, and maintenance of animals and plants in space and related environmental conditions. For specific topics in life sciences see *categories 52 through 55*.

20040081213 NASA Johnson Space Center, Houston, TX, USA


Preservation of Liquid Biological Samples

Putcha, Lakshmi, Inventor; Nimmagudda, Ramalingeshwara, Inventor; April 06, 2004; 12 pp.; In English Patent Info.: Filed 28 Jul. 2000; US-Patent-6,716,392; US-Patent-Appl-SN-630979; US-Patent-Appl-SN-007239; NASA-Case-MSC-22616-3; No Copyright; Avail: CASI; A03, Hardcopy

The present invention related to the preservation of a liquid biological sample. The biological sample is exposed to a preservative containing at least about 0.15 g of sodium benzoate and at least about 0.025 g of citric acid per 100 ml of sample. The biological sample may be collected in a vessel or an absorbent mass. The biological sample may also be exposed to a substrate and/or a vehicle.

Author

Liquids; Biology; Samples; Preserving



20040081249 NASA Langley Research Center, Hampton, VA, USA

Method and Apparatus for Determining Changes in Intracranial Pressure Utilizing Measurement of the Circumferential Expansion or Contraction of a Patient's Skull

Yos, William T., Inventor; Cantrell, John H., Jr., Inventor; June 08, 2004; 6 pp.; In English


Patent Info.: Filed 4 Apr. 2002; US-Patent-6,746,410; US-Patent-Appl-SN-121932; US-Case-LAR-15943-1; No Copyright; Avail: CASI; A02, Hardcopy

A method and apparatus for measuring changes in intracranial pressure (ICP) utilizing the variation of the surface wave propagation parameters of the patient's skull to determine the change in ICP. In one embodiment, the method comprises the steps of transmitting an ultrasonic bulk compressional wave onto the surface of the skull at a predetermined angle with respect to the skull so as to produce a surface wave, receiving the surface wave at an angle with respect tn the skull which is substantially the same as the predetermined angle and at a location that is a predetermined distance from where the ultrasonic bulk compressional wave was transmitted upon the skull, determining the retardation or advancement in phase of the received surface wave with respect to a reference phase, and processing the determined retardation or advancement in phase to

determine circumferential expansion or contraction of the skull and utilizing the determined circumferential change to determine the change in intracranial pressure.

Author

Compression Waves; Intracranial Pressure; Pressure Measurement



20040121001 NASA Langley Research Center, Hampton, VA, USA


Passive Fetal Heart Monitoring System

Bryant, Timothy D., Inventor; Wynkoop, Mark W., Inventor; Holloway, Nancy M. H., Inventor; Zuckerwar, Allan J., Inventor; June 15, 2004; 28 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 13 Feb. 2001; US-Patent-6,749,573; US-Patent-Appl-SN-784414; US-Patent-Appl-SN-182344; NASA-Case-LAR-15602-1; No Copyright; Avail: CASI; A03, Hardcopy

A fetal heart monitoring system preferably comprising a backing plate having a generally concave front surface and a generally convex back surface, and at least one sensor element attached to the concave front surface for acquiring acoustic fetal heart signals produced by a fetus within a body. The sensor element has a shape that conforms to the generally concave back surface of the backing plate. In one embodiment, the at least one sensor element comprises an inner sensor, and a plurality of outer sensors surrounding the inner sensor. The fetal heart monitoring system can further comprise a web belt, and a web belt guide movably attached to the web belt. The web belt guide being is to the convex back surface of the backing plate. Author

Heart; Monitors; Signal Transmission



52 AEROSPACE MEDICINE

Includes the biological and physiological effects of atmospheric and space flight (weightlessness, space radiation, acceleration, and altitude stress) on the human being; and the prevention of adverse effects on those environments. For psychological and behavioral effects of aerospace environments, see *53 Behavioral Sciences*. For the effects of space on animals and plants see *51 Life Sciences*.


20040120976 NASA Langley Research Center, Hampton, VA, USA

Non-Invasive Method of Determining Absolute Intracranial Pressure

Yost, William T., Inventor; Cantrell, John H., Jr., Inventor; Hargens, Alan E., Inventor; August 10, 2004; 8 pp.; In English; Original contains black and white illustrations; US-Patent-6,773,407; US-Patent-Appl-SN-263286; US-Patent-Appl-SN-371601; NASA-Case-LAR-16510-1; No Copyright; Avail: CASI; A02, Hardcopy

A method is presented for determining absolute intracranial pressure (ICP) in a patient. Skull expansion is monitored while changes in ICP are induced. The patient's blood pressure is measured when skull expansion is approximately zero. The measured blood pressure is indicative of a reference ICP value. Subsequently, the method causes a known change in ICP and measured the change in skull expansion associated therewith. The absolute ICP is a function of the reference ICP value, the known change in ICP and its associated change in skull expansion; and a measured change in skull expansion.

Medical Equipment; Pressure Measurement; Intracranial Pressure; Skull; Nonintrusive Measurement



61 COMPUTER PROGRAMMING AND SOFTWARE

Includes software engineering, computer programs, routines, algorithms, and specific applications, e.g., CAD/CAM. For computer software applied to specific applications, see also the associated category.

20040081250 NASA Ames Research Center, Moffett Field, CA, USA

System, Method and Apparatus for Discovering Phrases in a Database

McGreevy, Michael W., Inventor; April 13, 2004; 75 pp.; In English


Patent Info.: Filed 2 Mar. 2001; US-Patent-6,721,728; US-Patent-Appl-SN-800310; NASA-Case-ARC-14515-1; No Copyright; Avail: CASI; A04, Hardcopy

A phrase discovery is a method of identifying sequences of terms in a database. First, a selection of one or more relevant sequences of terms, such as relevant text, is provided. Next, several shorter sequences of terms, such as phrases, are extracted from the provided relevant sequences of terms. The extracted sequences of terms are then reduced through a culling process. A gathering process then emphasizes the more relevant of the extracted and culled sequences of terms and de-emphasizes the more generic of the extracted and culled sequences of terms. The gathering process can also include iteratively retrieving additional selections of relevant sequences (e.g., text), extracting and culling additional sequences of terms (e.g., phrases).

emphasizing and de-emphasizing extracted and culled sequences of terms and accumulating all gathered sequences of terms. The resulting gathered sequences of terms are then output.

Author

Data Bases; Identifying; Texts; Computer Programs



20040121003 NASA Marshall Space Flight Center, Huntsville, AL, USA

Generalized Fluid System Simulation Program


Majumdar, Alok Kumar, Inventor; Bailey, John W., Inventor; Schallhorn, Paul Alan, Inventor; Steadman, Todd E., Inventor; June 08, 2004; 35 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 7 May 1999; US-Patent-6,748,349; US-Patent-Appl-SN-313576; NASA-Case-MFS-31303-1; No Copyright; Avail: CASI; A03, Hardcopy

A general purpose program implemented on a computer analyzes steady state and transient flow in a complex fluid network, modeling phase changes, compressibility, mixture thermodynamics and external body forces such as gravity and centrifugal force. A preprocessor provides for the inter- active development of a fluid network simulation having nodes and branches. Mass, energy, and specie conservation equations are solved at the nodes, and momentum conservation equations are solved in the branches. Contained herein are subroutines for computing 'real fluid' thermodynamic and thermophysical properties for 12 fluids, and a number of different source options are provided for model- ing momentum sources or sinks in the branches. The system of equations describing the fluid network is solved by a hybrid numerical method that is a combination of the Newton-Raphson and successive substitution methods. Application and verification of this invention are provided through an example problem, which demonstrates that the predictions of the present invention compare most reasonably with test data.

Author

Computer Programs; Fluid Flow; Computerized Simulation; Gravitation; Centrifugal Force; Thermodynamic Properties



74 OPTICS

Includes light phenomena and the theory of optical devices; for specific optical devices see also 35 Instrumentation and Photography. For lasers see 36 Lasers and Masers.

20040120996 NASA Marshall Space Flight Center, Huntsville, AL, USA

Magnetic Symbology Reader


Schramm, Harry F., Inventor; Shih, William C. L., Inventor; Fitzpatrick, Gerald L., Inventor; Knisely, Craig, Inventor; June 08, 2004; 5 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 5 Aug. 2002; US-Patent-6,745,942; US-Patent-Appl-SN-214482; NASA-Case-MFS-31768-1; No Copyright; Avail: CASI; A01, Hardcopy

A magnetic symbology reader has a housing containing a polarized light source which directs light though a magneto-optic sensor onto a reflector which reflects light least one analyzer and into at least one camera. A view finder allows

the user to monitor the image on the sensor as seen by a viewfinder camera while a processor is coupled to possibly a second camera so that when an image is detected, the image from the camera may be processed by the processor to output information associated with the symbol to an external source. The analyzer and polarized light source provide contrast in the images detected by the sensor. A bias/erase coil located about the magneto-optic sensor can enhance or erase images on the sensor. Official Gazette of the U.S. Patent and Trademark Office

Magneto-Optics; Readers; Symbols; Sensors



20040191320 Naval Research Lab., USA

Method for Fabricating Metallic Mesh Infrared Optics

[2003]; 51 pp.; In English

Contract(s)/Grant(s): NAG5-7394; Navy-Case-84985; No Copyright; Avail: CASI; A04, Hardcopy

The purpose of the invention is to design and fabricate precise optical devices that can be used to filter or otherwise process infrared radiation. The improved precision of this new monolithic fabrication process, the clever designs - in the metal lattice geometries, the multiple layering of different geometries to comprise unique sets, the precise irregular, sub-wavelength spacing of these layers, and the precise testing of prototypes and intermediate stages - as well as the reliable modeling all enable the construction of filters that operate at shorter wavelengths, and increase the yield of each fabrication run while decreasing the fabrication time and cost.

Author

Optical Equipment; Mesh; Optical Filters; Metals; Fabrication; Optical Materials; Infrared Radiation

76 SOLID-STATE PHYSICS

Includes condensed matter physics, crystallography, and superconductivity. For related information see also 33 Electronics and Electrical Engineering; and 36 Lasers and Masers.

20040120994 NASA Glenn Research Center, Cleveland, OH, USA

Lateral Movement of Screw Dislocations During Homoepitaxial Growth and Devices Yielded Therefrom Free of the Detrimental Effects of Screw Dislocations


Neudeck, Philip G., Inventor; Powell, J. Anthony, Inventor; August 31, 2004; 37 pp.; In English; Original contains black and white illustrations

Patent Info.: Filed 10 Oct. 2002; US-Patent-6,783,592; US-Patent-Appl-SN-268749; NASA-Case-LEW-17237-1; No Copyright; Avail: CASI; A03, Hardcopy

The present invention is related to a method that enables and improves wide bandgap homoepitaxial layers to be grown on axis single crystal substrates, particularly SiC. The lateral positions of the screw dislocations in epitaxial layers are predetermined instead of random, which allows devices to be reproducibly patterned to avoid performance degrading crystal defects normally created by screw dislocations.

Official Gazette of the U.S. Patent and Trademark Office

Crystal Growth; Epitaxy; Screw Dislocations; Single Crystals



Subject Term Index

ACCELEROMETERS

Multi-Functional, Micro Electromechanical Silicon Carbide Accelerometer – 5

ALPHA PARTICLES

Very High Efficiency, Miniaturized, Long-Lived Alpha Particle Power Source Using Diamond Devices for Extreme Space Environments – 7

ATOMIZERS

Method for Forming MEMS-Based Spinning Nozzle -2

BAGGAGE

Article Screening System - 1

BARRIER LAYERS

Multilayer Article Characterized by Low Coefficient of Thermal Expansion Outer Layer -3

BIOINSTRUMENTATION

Retinal Light Processing Using Carbon Nanotubes - 13

BIOLOGY

Preservation of Liquid Biological Samples – 17

CARBON NANOTUBES

Retinal Light Processing Using Carbon Nanotubes - 13

Single-element Electron-transfer Optical Detector System -13

CATALYSTS

Process for Coating Substrates with Catalytic Materials – 4

CENTRIFUGAL FORCE

Generalized Fluid System Simulation Program – 20

CLAMPS

Force-Measuring Clamp - 15

COATINGS

Dual Use Corrosion Inhibitor and Penetrant for Anomaly Detection in Neutron/X Radiography – 3

COATING

Process for Coating Substrates with Catalytic Materials – 4

COMPRESSION WAVES

Method and Apparatus for Determining Changes in Intracranial Pressure Utilizing Measurement of the Circumferential Expansion or Contraction of a Patient's Skull – 17

COMPUTER PROGRAMS

Generalized Fluid System Simulation Program -20

System, Method and Apparatus for Discovering Phrases in a Database - 19

COMPUTERIZED SIMULATION

Generalized Fluid System Simulation Program – 20

CORROSION PREVENTION

Dual Use Corrosion Inhibitor and Penetrant for Anomaly Detection in Neutron/X Radiography – 3

CRYOGENICS

Methods of Testing Thermal Insulation and Associated Test Apparatus – 16

CRYSTAL GROWTH

Lateral Movement of Screw Dislocations During Homoepitaxial Growth and Devices Yielded Therefrom Free of the Detrimental Effects of Screw Dislocations – 22

DATA BASES

System, Method and Apparatus for Discovering Phrases in a Database – 19

DIAGRAMS

Auto-Adjustable Tool for Self-Reacting and Conventional Friction Stir Welding – 15

DIAMOND FILMS

Very High Efficiency, Miniaturized, Long-Lived Alpha Particle Power Source Using Diamond Devices for Extreme Space Environments – 7

ELECTRIC POWER SUPPLIES

Very High Efficiency, Miniaturized, Long-Lived Alpha Particle Power Source Using Diamond Devices for Extreme Space Environments — 7

ELECTROLYTIC CELLS

Cross Cell Sandwich Core - 7

ELECTRON COUNTERS

Single-element Electron-transfer Optical Detector System - 13

ELECTRON TRANSFER

Multi-Element Electron-Transfer Optical Detector System - 9

Single-element Electron-transfer Optical Detector System - 13

ENHANCED VISION

Retinal Light Processing Using Carbon Nanotubes - 13

EPITAXY

Lateral Movement of Screw Dislocations During Homoepitaxial Growth and Devices Yielded Therefrom Free of the Detrimental Effects of Screw Dislocations – 22

FABRICATION

Gas Sensors Using SiC Semiconductors and Method of Fabrication Thereof - 14

Method for Fabricating Metallic Mesh Infrared Optics -22

Method for Forming MEMS-Based Spinning Nozzle - 2

FERROMAGNETIC MATERIALS

Ferromagnetic Conducting Lignosulfonic Acid-doped Polyaniline Nanocomposites – 4

FLUID FLOW

Generalized Fluid System Simulation Program – 20

FRICTION STIR WELDING

Auto-Adjustable Tool for Self-Reacting and Conventional Friction Stir Welding – 15

FUEL INJECTION

Method for Forming MEMS-Based Spinning Nozzle - 2

FUEL SPRAYS

Method for Forming MEMS-Based Spinning Nozzle - 2

FULLERENES

Protective Fullerene (C60) Packaging System for Microelectromechanical Systems Applications – 6

GAS DETECTORS

Gas Sensors Using SiC Semiconductors and Method of Fabrication Thereof - 14

GRAVITATION

Generalized Fluid System Simulation Program – 20

HEALTH

Thermodynamic Pressure/Temperature Transducer Health Check – 11

HEART

Passive Fetal Heart Monitoring System - 18

HEAT TRANSFER

Apparatus and Method for Thermal Performance Testing of Pipelines and Piping Systems – 8

HETERODYNING

Heterodyne Interferometer with a Phase Modulated Source - 12

IDENTIFYING

System, Method and Apparatus for Discovering Phrases in a Database - 19

IMAGE PROCESSING

Video Image Tracking Engine - 14

IMAGING TECHNIQUES

Article Screening System - 1

INFRARED RADIATION

Method for Fabricating Metallic Mesh Infrared Optics - 22

INTERFEROMETERS

Heterodyne Interferometer with a Phase Modulated Source - 12

INTRACRANIAL PRESSURE

Method and Apparatus for Determining Changes in Intracranial Pressure Utilizing Measurement of the Circumferential Expansion or Contraction of a Patient's Skull – 17

Method and Apparatus for Non-Invasive Measurement of Changes in Intracranial Pressure — 10

Non-Invasive Method of Determining Absolute Intracranial Pressure – 19

LIQUIDS

Preservation of Liquid Biological Samples – 17

LITHIUM BATTERIES

Method for Manufacturing Thin-film Lithium Microbatteries – 6

MAGNETO-OPTICS

Magnetic Symbology Reader - 21

MANUFACTURING

Method for Manufacturing Thin-film Lithium Microbatteries – 6

Multi-Functional, Micro Electromechanical Silicon Carbide Accelerometer - 5

Rare Earth Optical Temperature Sensor - 11

MEDICAL EQUIPMENT

Method and Apparatus for Non-Invasive Measurement of Changes in Intracranial Pressure — 10

Non-Invasive Method of Determining Absolute Intracranial Pressure – 19

MESH

Method for Fabricating Metallic Mesh Infrared Optics - 22

METALS

Method for Fabricating Metallic Mesh Infrared Optics - 22

MICROELECTROMECHANICAL SYSTEMS

Method for Forming MEMS-Based Spinning Nozzle - 2

Multi-Functional, Micro Electromechanical Silicon Carbide Accelerometer – 5

Protective Fullerene (C60) Packaging System for Microelectromechanical Systems Applications – 6

MONITORS

Passive Fetal Heart Monitoring System - 18

Self-Activating System and Method for Alerting When an Object or a Person is Left Unattended – 9

NANOCOMPOSITES

Ferromagnetic Conducting Lignosulfonic Acid-doped Polyaniline Nanocomposites -4

NONDESTRUCTIVE TESTS

Synchronized Electronic Shutter System and Method for Thermal Nondestructive Evaluation -5

NONINTRUSIVE MEASUREMENT

Method and Apparatus for Non-Invasive Measurement of Changes in Intracranial Pressure – 10

Non-Invasive Method of Determining Absolute Intracranial Pressure – 19

OPTICAL EQUIPMENT

Method for Fabricating Metallic Mesh Infrared Optics - 22

Multi-Element Electron-Transfer Optical Detector System - 9

OPTICAL FILTERS

Method for Fabricating Metallic Mesh Infrared Optics - 22

OPTICAL MATERIALS

Method for Fabricating Metallic Mesh Infrared Optics - 22

OPTICAL MEASURING INSTRUMENTS

Rare Earth Optical Temperature Sensor - 11

PACKAGING

Protective Fullerene (C60) Packaging System for Microelectromechanical Systems Applications – 6

PENETRANTS

Dual Use Corrosion Inhibitor and Penetrant for Anomaly Detection in Neutron/X Radiography – 3

PERFORMANCE TESTS

Apparatus and Method for Thermal Performance Testing of Pipelines and Piping Systems — 8

PHASE MODULATION

Heterodyne Interferometer with a Phase Modulated Source -12

PIPELINES

Apparatus and Method for Thermal Performance Testing of Pipelines and Piping Systems - 8

POLYIMIDES

Heat, Moisture and Chemical Resistant Polyimide Compositions and Methods for Making and Using Them - 2

PRESERVING

Preservation of Liquid Biological Samples – 17

PRESSURE MEASUREMENT

Method and Apparatus for Determining Changes in Intracranial Pressure Utilizing Measurement of the Circumferential Expansion or Contraction of a Patient's Skull – 17

Method and Apparatus for Non-Invasive Measurement of Changes in Intracranial Pressure – 10

Non-Invasive Method of Determining Absolute Intracranial Pressure – 19

PRESSURE SENSORS

Thermodynamic Pressure/Temperature Transducer Health Check – 11

RADIATION DETECTORS

Multi-Element Electron-Transfer Optical Detector System – 9

RADIOGRAPHY

Dual Use Corrosion Inhibitor and Penetrant for Anomaly Detection in Neutron/X Radiography – 3

RARE EARTH ELEMENTS

Rare Earth Optical Temperature Sensor - 11

READERS

Magnetic Symbology Reader - 21

RFTINA

Retinal Light Processing Using Carbon Nanotubes - 13

SAFETY

Self-Activating System and Method for Alerting When an Object or a Person is Left Unattended - 9

SAMPLES

Preservation of Liquid Biological Samples – 17

SCREW DISLOCATIONS

Lateral Movement of Screw Dislocations During Homoepitaxial Growth and Devices Yielded Therefrom Free of the Detrimental Effects of Screw Dislocations – 22

SEMICONDUCTORS (MATERIALS)

Gas Sensors Using SiC Semiconductors and Method of Fabrication Thereof - 14

SENSORS

Magnetic Symbology Reader - 21

SHUTTERS

Synchronized Electronic Shutter System and Method for Thermal Nondestructive Evaluation – 5

SIGNAL TRANSMISSION

Passive Fetal Heart Monitoring System - 18

SILICATES

Multilayer Article Characterized by Low Coefficient of Thermal Expansion Outer Layer $-\ 3$

SILICON CARBIDES

Gas Sensors Using SiC Semiconductors and Method of Fabrication Thereof - 14

Multi-Functional, Micro Electromechanical Silicon Carbide Accelerometer – 5

SINGLE CRYSTALS

Lateral Movement of Screw Dislocations During Homoepitaxial Growth and Devices Yielded Therefrom Free of the Detrimental Effects of Screw Dislocations – 22

SKULL

Non-Invasive Method of Determining Absolute Intracranial Pressure – 19

SPRAY NOZZLES

Method for Forming MEMS-Based Spinning Nozzle - 2

STEREOSCOPY

Article Screening System - 1

STRAIN GAGES

Force-Measuring Clamp - 15

SUBSTRATES

Process for Coating Substrates with Catalytic Materials - 4

SULFONIC ACID

Ferromagnetic Conducting Lignosulfonic Acid-doped Polyaniline Nanocomposites – 4

SYMBOLS

Magnetic Symbology Reader - 21

SYNCHRONIZERS

Synchronized Electronic Shutter System and Method for Thermal Nondestructive Evaluation - 5

SYNTHESIS (CHEMISTRY)

Heat, Moisture and Chemical Resistant Polyimide Compositions and Methods for Making and Using Them - 2

TEMPERATURE SENSORS

Rare Earth Optical Temperature Sensor – 11

TEXTS

System, Method and Apparatus for Discovering Phrases in a Database - 19

THERMAL ANALYSIS

Synchronized Electronic Shutter System and Method for Thermal Nondestructive Evaluation - 5

THERMAL EXPANSION

Multilayer Article Characterized by Low Coefficient of Thermal Expansion Outer Layer $-\ 3$

THERMAL INSULATION

Methods of Testing Thermal Insulation and Associated Test Apparatus -16

THERMODYNAMIC PROPERTIES

Generalized Fluid System Simulation Program – 20

THERMODYNAMICS

Thermodynamic Pressure/Temperature Transducer Health Check - 11

THERMOMETERS

Thermodynamic Pressure/Temperature Transducer Health Check - 11

HIN FII MS

Method for Manufacturing Thin-film Lithium Microbatteries – 6

VIDEO DATA

Video Image Tracking Engine - 14

VIDEO EQUIPMENT

Video Image Tracking Engine - 14

WALLS

Cross Cell Sandwich Core - 7

WARNING SYSTEMS

Self-Activating System and Method for Alerting When an Object or a Person is Left Unattended - 9

X RAY IMAGERY

Article Screening System - 1

ZIRCONIUM OXIDES

Multilayer Article Characterized by Low Coefficient of Thermal Expansion Outer Layer $-\ 3$

Personal Author Index

Augustynowicz, Stanislaw D.

Apparatus and Method for Thermal Performance Testing of Pipelines and Piping Systems – 8

Bailey, John W.

Generalized Fluid System Simulation Program – 20

Berry, Brian

Ferromagnetic Conducting Lignosulfonic Acid-doped Polyaniline Nanocomposites – 4

Book, Michael L.

Video Image Tracking Engine - 14

Bryan, ThomasC.

Video Image Tracking Engine - 14

Bryant, Timothy D.

Passive Fetal Heart Monitoring System - 18

Bugga, Ratnakumar V.

Method for Manufacturing Thin-film Lithium Microbatteries – 6

Cantrell, John H., Jr.

Method and Apparatus for Determining Changes in Intracranial Pressure Utilizing Measurement of the Circumferential Expansion or Contraction of a Patient's Skull – 17

Method and Apparatus for Non-Invasive Measurement of Changes in Intracranial Pressure — 10

Non-Invasive Method of Determining Absolute Intracranial Pressure — 19

Carter, Robert W.

Auto-Adjustable Tool for Self-Reacting and Conventional Friction Stir Welding - 15

Chubb, Donald L.

Rare Earth Optical Temperature Sensor - 11

Devoe, Richard T.

Thermodynamic Pressure/Temperature Transducer Health Check – 11

Dubovitsky, Serge

Heterodyne Interferometer with a Phase Modulated Source – 12

Eckhoff, Anthony

Thermodynamic Pressure/Temperature Transducer Health Check - 11

Edwards, William Christopher

Self-Activating System and Method for Alerting When an Object or a Person is Left Unattended – 9

Fernandez, Kenneth R.

Article Screening System - 1

Fesmire, James E.

Apparatus and Method for Thermal Performance Testing of Pipelines and Piping Systems - 8

Fishman, Harvey

Retinal Light Processing Using Carbon Nanotubes – 13

Fitzpatrick, Gerald L.

Magnetic Symbology Reader - 21

Fleurial, Jean-Pierre

Very High Efficiency, Miniaturized, Long-Lived Alpha Particle Power Source Using Diamond Devices for Extreme Space Environments – 7

Ford, Donald B.

Cross Cell Sandwich Core - 7

Hall, Phillip B.

Dual Use Corrosion Inhibitor and Penetrant for Anomaly Detection in Neutron/X Radiography – 3

Hargens, Alan E.

Non-Invasive Method of Determining Absolute Intracranial Pressure – 19

Holloway, Nancy M. H.

Passive Fetal Heart Monitoring System – 18

Howard, Richard T.

Video Image Tracking Engine - 14

Hunter, Gary W.

Gas Sensors Using SiC Semiconductors and Method of Fabrication Thereof - 14

Immer, Christopher D.

Thermodynamic Pressure/Temperature Transducer Health Check - 11

Jenkins, Phillip

Rare Earth Optical Temperature Sensor – 11

Jordan, Jeffrey D.

Multi-Element Electron-Transfer Optical Detector System - 9

Single-element Electron-transfer Optical Detector System – 13

Klelin, Ric J.

Process for Coating Substrates with Catalytic Materials – 4

Knisely, Craig

Magnetic Symbology Reader - 21

Kolawa, Elizabeth A.

Very High Efficiency, Miniaturized, Long-Lived Alpha Particle Power Source Using Diamond Devices for Extreme Space Environments – 7

Lee, Kang N.

Multilayer Article Characterized by Low Coefficient of Thermal Expansion Outer Layer $-\ 3$

Leng, Theodore

Retinal Light Processing Using Carbon Nanotubes - 13

Loftus, David J.

Retinal Light Processing Using Carbon Nanotubes – 13

Mack, Terry L.

Self-Activating System and Method for Alerting When an Object or a Person is Left Unattended – 9

Majumdar, Alok Kumar

Generalized Fluid System Simulation Program – 20

McGreevy, Michael W.

System, Method and Apparatus for Discovering Phrases in a Database - 19

Medelius, Pedro J.

Thermodynamic Pressure/Temperature Transducer Health Check - 11

Modlin, Edward A.

Self-Activating System and Method for Alerting When an Object or a Person is Left Unattended – 9

Nagy, Zeltan F.

Apparatus and Method for Thermal Performance Testing of Pipelines and Piping Systems - 8

Neudeck, Philip G.

Gas Sensors Using SiC Semiconductors and Method of Fabrication Thereof - 14

Lateral Movement of Screw Dislocations During Homoepitaxial Growth and Devices Yielded Therefrom Free of the Detrimental Effects of Screw Dislocations – 22

Nimmagudda, Ramalingeshwara

Preservation of Liquid Biological Samples – 17

Novak, Howard L.

Dual Use Corrosion Inhibitor and Penetrant for Anomaly Detection in Neutron/X Radiography - 3

Nunnelee, Mark

Force-Measuring Clamp - 15

Okojie, Robert S.

Method for Forming MEMS-Based Spinning Nozzle - 2

Multi-Functional, Micro Electromechanical Silicon Carbide Accelerometer - 5

Olivas, John D.

Protective Fullerene (C60) Packaging System for Microelectromechanical Systems Applications – 6

Patel, Jagdishbhai U.

Very High Efficiency, Miniaturized, Long-Lived Alpha Particle Power Source Using Diamond Devices for Extreme Space Environments – 7

Pater, Ruth H.

Heat, Moisture and Chemical Resistant Polyimide Compositions and Methods for Making and Using Them – 2

Powell, J. Anthony

Lateral Movement of Screw Dislocations During Homoepitaxial Growth and Devices Yielded Therefrom Free of the Detrimental Effects of Screw Dislocations – 22

Putcha, Lakshmi

Preservation of Liquid Biological Samples – 17

Schallhorn, Paul Alan

Generalized Fluid System Simulation Program – 20

Schramm, Harry F.

Magnetic Symbology Reader - 21

Schryer, David R.

Process for Coating Substrates with Catalytic Materials -4

Shih, William C. L.

Magnetic Symbology Reader - 21

Starr, Stanley O.

Thermodynamic Pressure/Temperature Transducer Health Check – 11

Steadman, Todd E.

Generalized Fluid System Simulation Program – 20

Upchurch, Billy T.

Process for Coating Substrates with Catalytic Materials -4

Viswansthan, Tito

Ferromagnetic Conducting Lignosulfonic Acid-doped Polyaniline Nanocomposites – 4

West, William C.

Method for Manufacturing Thin-film Lithium Microbatteries – 6

Whitacre, Jay F.

Method for Manufacturing Thin-film Lithium Microbatteries – 6

Winfree, William P.

Synchronized Electronic Shutter System and Method for Thermal Nondestructive Evaluation – 5

Wynkoop, Mark W.

Passive Fetal Heart Monitoring System - 18

Yos, William T.

Method and Apparatus for Determining Changes in Intracranial Pressure Utilizing Measurement of the Circumferential Expansion or Contraction of a Patient's Skull – 17

Yost, William T.

Method and Apparatus for Non-Invasive Measurement of Changes in Intracranial Pressure – 10

Non-Invasive Method of Determining Absolute Intracranial Pressure – 19

Zalameda, Joseph N.

Synchronized Electronic Shutter System and Method for Thermal Nondestructive Evaluation - 5

Zuckerwar, Allan J.

Passive Fetal Heart Monitoring System – 18

Public Availability of Copies of Patents

Copies of U.S. patents may be purchased directly from the U.S. Patent and Trademark Office, Washington, D.C. 20231 at \$3.00 per copy. When ordering patents, the U.S. Patent Number should be used, and payment must be remitted in advance, preferably by money order or check payable to the Commissioner of Patents and Trademarks. Prepaid purchase coupons for ordering are also available from the Patent and Trademark Office.

Copies of U.S. patents may also be purchased on–line from the U.S. Patent and Trademark Office via its web site at http://www.uspto.gov. Additionally, patents may be viewed for free online at the U.S. Patent and Trademark Office web site.

Licenses for Commercial Use: Inquiries and Applications for License

NASA inventions abstracted in this bibliography are generally available for nonexclusive or exclusive licensing in accordance with the Department of Commerce Patent License Regulations (37 CFR Part 404). However, the availability for licensing of individual inventions may have changed since the publication of this bibliography. Applications for licensing NASA patents must be submitted in writing to the Patent Counsel of the NASA installation having cognizance of the specific invention. All NASA patent licenses shall be by express written instruments executed by the NASA General Counsel.

Inquiries concerning the NASA Patent Licensing Program or the availability of licenses for the commercial use of NASA—owned inventions covered by U.S. patents or pending applications for patent should be forwarded to the NASA Patent Counsel of the NASA installation having cognizance of the specific invention, or the Associate General Counsel for Intellectual Property, Commercial and International Law, National Aeronautics and Space Administration, Washington, D.C. 20546. Inquiries should refer to the NASA Case Number, the Title of the Invention, and the U.S. Patent Number assigned to the invention as shown in this bibliography. Patent applications available for licensing are periodically advertised in the Federal Register.

The NASA Patent Counsel having cognizance of the invention is determined by the first three letters or prefix of the NASA Case Number assigned to the invention. The addresses and contact numbers for NASA Patent Counsels are listed alongside the NASA Case Number prefix letters in the following table.

Center Patent Counsels

HQN-xxxxx NASA Headquarters

Suite No. 9W39-C, 300 E Street SW

Washington, DC 20546-0001

202-358-2041 (Phone) 202-358-4341 (Fax)

ARC-xxxxx Ames Research Center

Mail Code 202A-4

Moffett Field, CA 94035

650-604-0887 (Phone) 650-604-2767 (Fax)

DRC-xxxxx Dryden Flight Research Center

PO Box 273, Mail Stop 4839

Edwards, CA 93523-0273

No assigned Patent Counsel - services provided by NASA Management Office -JPL

LEW-xxxxx Glenn Research Center at Lewis Field

Mail Code 500-118

21000 Brookpark Rd, Cleveland, OH 44135-3191 216-433-5756 (Phone) 216-433-6790 (Fax)

GSC-xxxxx Goddard Space Flight Center

Mail Code 503

Greenbelt, MD 20771-0001

301-286-2385 (Phone) 301-286-9502 (Fax)

MSC-xxxxx Lyndon B. Johnson Space Center

Mail Code AL

2101 NASA Road 1, Houston, TX 77058-8452 281-483-1013 (Phone) 281-244-8452 (Fax)

KSC-xxxxx John F. Kennedy Space Center

Mail Code CC-A

Kennedy Space Center, FL 32899-0001 321-867-3058 (Phone) 321-867-1817 (Fax)

LAR-xxxxx Langley Research Center

Mail Code 141

Hampton, VA 23681-2199

757-864-3955 (Phone) 757-864-9190 (Fax)

MFS-xxxxx George C. Marshall Space Flight Center

Mail Code LS01

Marshal Space Flight Center, AL 35812-0001 256-544-0018 (Phone) 256-544-0258 (Fax)

NPO-xxxxx NASA Management Office-JPL

Mail Code 180-200

4800 Oak Grove Dr, Pasadena, CA 91109 818-354-7770 (Phone) 818-393-3160 (Fax)

SSC-xxxxx John C. Stennis Space Center

Mail Code HA30

Stennis Space Center, MS 39529-6000

No assigned Patent Counsel - services provided by Kennedy Space Center

Report Documentation Page

1. Report No.	2. Government Accession No.	3. Recipient's Catalo	g No.	
NASA/SP—2005-7039/SUPPL65				
4. Title and Subtitle		5. Report Date		
NASA Patent Abstracts		January 2005		
A Continuing Bibliography (Su	applement 65)	6. Performing Organ	ization Code	
7. Author(s)		8. Performing Organ	ization Report No.	
		10. Work Unit No.		
9. Performing Organization Name and Ad	ldress			
NASA Scientific and Technical	l Information Program Office	11. Contract or Grant	No.	
	C			
12. Sponsoring Agency Name and Address	s	13. Type of Report an	d Period Covered	
National Aeronautics and Spac	e Administration	Special Public	ation	
Langley Research Center		14. Sponsoring Agence	cy Code	
Hampton, VA 23681				
15. Supplementary Notes				
16. Abstract				
This report lists NASA patent a	abstracts recently announced in the	ne NASA STI Databas	se.	
This report lists 14 15/11 patient destructs recently announced in the 14/15/11 5/11 Butdouse.				
17. Key Words (Suggested by Author(s))	18. Distribution S	18. Distribution Statement		
Bibliographies	Unclassific	Unclassified - Unlimited		
Patent Policy		ategory - 82		
NASA Programs	Subject Ca			
	20. Security Classif. (of this page)	21. No. of Pages	22. Price	
Unclassified	Unclassified	35		
Chemodifica	J110100011100	1 33	l	